

FISCHER ASSAY OIL-YIELD HISTOGRAM, WIRE-LINE WELL LOGS, AND GENERALIZED LITHOLOGIC LOG FROM CORE HOLE EOS-6, ELKO COUNTY, NEVADA

Ву S.W. Moore

1983

PLATE 7 Core Hole EOS-6

U.S. GEOLOGICAL SURVEY CORE HOLE EOS-6

LOCATION

NE SW SE sec. 22, T. 34 N., R. 55 E., Mount Diablo Meridian, Elko County, Nevada; from southeast section corner, located approximately 800 ft north and 1850 ft west.

APPROXIMATE ELEVATION = 5260 ft

TOTAL DEPTH = 192.0 ft

HOLE DIAMETER (Drilled) = 3.0 in.

CORE SIZE: NO (1.875-inch diameter)

DRILLED BY: Toly Exploration and Drilling, Salt Lake City, Utah

DRILLING MEDIUM: Air mist and bentonite gel

DEPTH TO CORE POINT = 112.5 ft

DATE STARTED: 11/21/81

DATE COMPLETED: 11/24/81

WELL-SITE GEOLOGISTS: S. W. Moore and R. D. Dockter

WIRE-LINE WELL LOGS

Logger: White Dog Exploration Co., Salt Lake City, Utah Date Logged: 11/24/81

Logged Depth: 191.0 ft

Type of Log	Abbreviation	Logging Speed (feet/minute)	Time Constar
Gamma Ray	GR	15	2
Gamma-Gamma Density	GGD	10	1
Resistance	R	15	
Caliper	CAL	15	

Remarks: Original scale of logging was at linch = 5 ft. The resistance log is an uncalibrated log; relative resistance increases to the right. The horizontal scale of the gamma-gamma density log scale changes at a depth of 107 ft (water level). Density increases to the right.

HOLE CONDITIONS

Depth of casing = 18.0 ft


Empty hole 0-107.0 ft; fluid (water) level at 107.0 ft Bad hole conditions (variable hole diameter—see caliper log)

LITHOLOGIC UNITS PENETRATED

Eocene and Oligocene(?) Elko Formation-member 4 (siltstone and oil shale member) and member 2 (oil shale member). Average dip of bedding

FISCHER ASSAYS BY

L. G. Trudell, Laramie Energy Technology Center, Laramie, Wyoming, using the modified Fischer retort method.



This report has not been edited for conformity with U. S. Geological Survey editorial standards or stratigraphic nomenclature.